

G EUROPROP

Lightweight shoring with high load capacity.

Alsina



■ Description

The Alsina Europrop G are props with an extension device according to the standard EN 1065 with integrated safety system. They serve as vertical prop for temporary structures. They also come with a quick release system which reduces their removal time.

■ Components and accessories

- Optional quick release system.
- Tripods for assembly.

■ Compatible

- Any system of roofs up to 5 meters high.

■ Frequent uses

- Props for supporting slabs and hanging beams.
- Ideal for residential or commercial construction, with slabs from 100 mm to 500 mm thick.

■ Properties

- Prop in compliance with EN 1065 standard.
- New quick-release system reduces removal time.
- High bearing capacity.
- Failsafe. For safety reasons, the Alsina props come equipped with a safety anti-separation device that prevents the tube from coming loose and falling.
- 10 cm of clearance with the prop closed as a safety measure against hands getting crushed.
- Long-life galvanized structure.
- Light weight in relation to its high load capacity.
- Enables optimizing the number of props on site.
- Models with and without load release.

Prop	Height (m) max. / min.	Weight (Kg) No rel. / Rel.	Load (kN)
G30	3.0 / 1.8	12.7 / 13.6	20.0 / 30.0
G40	4.0 / 2.3	17.8 / 18.3	20.0 / 30.0
G50	5.0 / 2.8	25.2	20.0 / 30.0